

Elevate your style and comfort with Haiku Luxe Indoor fans. Available in a variety of bold finishes, these fans establish a new standard for quality, design, technology, and convenience.

QUALITY, ELEGANCE, AND EFFICIENCY

- Aerofoils Aircraft-grade aluminium; 1.3m, 1.5m, or 2.1m fan sweep
- Finishes Brushed or polished metal or powder coat
- Motor EC motor with digital inverter drive
- Controls Remote control, Haiku mobile app¹, or 0–10 V module (optional with universal mount)
- Onboard Sensors Ambient and surface temperature, relative humidity, and passive infrared sensors enable SenseME® technology
- Environment Indoor use only
- Accessories Haiku Light Kit. Optional extension tube lengths and a Stabiliser Kit are available for ceilings 4.3 metres or taller (special order)

| Technical Specifications — Universal Mount | | | | | | |
|--|---------------------------------|---------------------------------|--------|---------------------------------|--|--|
| Diameter of fan sweep (A) | 1321mm | 1524mm | | 2134mm | | |
| Model number ² | S3127-X2-AX-XX-02- C-01-FXXX | S3150-X2-AX-XX-02- C-01-FXXX | | B3213-X4-XX-XX-02- D-01-FXXX | | |
| Weight ³ | 7 kg | 8 kg | | 11.8 kg | | |
| Watts (min/max) | 2.1/20.7 W | 1.9/26.8 W | | 4.2/53.7 W | | |
| Operating voltage | 100-240 VAC, 1 Ф, 50-60 Hz | | | | | |
| Max speed (7 speeds) | 200 RPM | | | 135 RPM | | |
| Sound level at max speed4 | < 35 dBA | | | | | |
| Included extension tubes | 508mm | | 813mm | | | |
| Height (B)⁵ | 721mm | | 1026mm | | | |
| Optional extension tubes ⁶ | 178mm | 1219mm | | 1524mm | | |
| Height (B)⁵ | 406mm | 1433mm | | 1737mm | | |

| Technical Specifications — Standard Mount | | | | | | | |
|---|-----------------------------|-----------------------------|--|--|--|--|--|
| Diameter of fan sweep (A) | 1321mm | 1524mm | | | | | |
| Model number ² | S3127-A2-AX-XX-02-C-01-FXXX | S3150-A2-AX-XX-02-C-01-FXXX | | | | | |
| Weight ³ | 7.5 kg | 8.4 kg | | | | | |
| Watts (min/max) | 2.1/20.7 W | 1.9/26.8 W | | | | | |
| Operating voltage | 100-240 VAC, 1 Ф, 50-60 Hz | | | | | | |
| Max speed (7 speeds) | 200 RPM | | | | | | |
| Sound level at max speed ⁴ | < 35 dBA | | | | | | |

| Technical Specifications — Low Profile Mount | | | | | | |
|--|-----------------------------|-----------------------------|--|--|--|--|
| Diameter of fan sweep (A) | 1321mm | 1524mm | | | | |
| Model number ² | S3127-S0-AX-XX-02-C-01-FXXX | S3150-S0-AX-XX-02-C-01-FXXX | | | | |
| Weight ³ | 7.5 kg | 8.4 kg | | | | |
| Watts (min/max) | 2.2/15.6 W | 1.9/18.4 W | | | | |
| Operating voltage | 100-240 VAC, 1 Ф, 50-60 Hz | | | | | |
| Max speed (7 speeds) | 177 RPM | | | | | |
| Sound level at max speed ⁴ | < 35 dBA | | | | | |


SenseME Technology and the Haiku app are supported by Android and iOS. All specifications are subject to change without notice.




| Aerofoil Finishes | | | | | | |
|-----------------------|----------------------|-----------------|----------------------|--|--|--|
| F421 | F523 | F537 | F531 | | | |
| Polished Aluminium | Brushed Copper | Brushed Gold | Brushed Aluminium | | | |
| F470 | F471 | АВ | AW | | | |
| Satin Nickel | Oil-Rubbed Bronze | Black* | White* | | | |

* Black and White airfoil finishes only available in 2.1m diameter.







Low Profile Mount 312mm







Flat ceilings as low as 2.4m



Service the consideration of the relative price of the consideration of